

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
26 May 2005 (26.05.2005)

PCT

(10) International Publication Number
WO 2005/048001 A1

(51) International Patent Classification⁷: **G05G 1/14**,
B60T 7/04, B60K 26/00, 23/02

(21) International Application Number:
PCT/CA2004/001959

(22) International Filing Date:
15 November 2004 (15.11.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/519,500 13 November 2003 (13.11.2003) US

(71) Applicant (for all designated States except US): **INTIER
AUTOMOTIVE CLOSURES INC.** [CA/CA]; 521 New-
park Boulevard, Newmarket, Ontario L3Y 4X7 (CA).

(72) Inventors; and


(75) Inventors/Applicants (for US only): **DJORDJEVIC**,
Nebojsa [CA/CA]; 1111 Steeles Avenue West, Apt.
607, Toronto, Ontario M2R 3M9 (CA). **OLICHWIER**,
Richard [CA/CA]; 3 Norbert Road, Brampton, Ontario
L6Y 2J9 (CA).

(74) Agents: **PORAT**, Alex et al.; Magna International Inc.,
337 Magna Drive, Aurora, Ontario L4G 7K1 (CA).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.

[Continued on next page]

(54) Title: MOVEABLE CONTROL PEDAL ASSEMBLY



(57) Abstract: A moveable control pedal assembly includes a pedal carriage to which a pedal arm is mounted. The carriage can be moved forward and backward via threaded extender rods which engage the pedal carriage to move it along the extender rods when they are rotated by a suitable drive means. A threaded control rod, extending between the pedal arm and a control device, such as a hydraulic cylinder or control cable, rotates with the extender rods and allows movement of the pedal carriage and pedal arm without altering the mechanical advantage provided by the pedal arm and without altering the lateral positioning of the control rod.